



- NOTES:**
1. Towed by 100hp Tractor with 21 Spline 1000 rpm PTO shaft
 2. Overall width across rear tires is 102"
 3. Re-circulating / Discharge Pump is 1,000 gpm at 20' head
 4. Peak collection rate with flooded head is 1,000 gpm
 5. Vacuum tank is 1800 usg capacity with 1,600 usable
 6. Vacuum system is protected by double relief system
 7. Vacuum head contains (2) 400gpm run dry collection pumps
 8. Truck mounted version is available
 9. Brakes are hydraulic disc type, activated by tractor hydraulic system or electric over hydraulic system

REV	BY	REVISION	DATE	ITEM QTY/PART NO.	DESCRIPTION	MATERIAL	SIZE
REV 1	ASST/RL	T1800	DEC 30 2020				
BURLINGTON NextGen Process Systems ONTARIO CANADA				TITLE: T1800 DIMENSIONAL DRAWING DRAWN: R.M. CHECKED: D.V. SCALE: FULL TOLERANCES UNLESS OTHERWISE SPECIFIED: * DECIMAL DIM. = ±.005 (0.15mm) ** FRACTIONAL DIM. = ±.010 (0.25mm) DIMENSIONS ARE IN INCHES UNLESS NOTED OTHERWISE			
THE INFORMATION CONTAINED HEREIN IS THE PROPERTY OF NEXTGEN PROCESS SYSTEMS. IT IS TO BE USED ONLY FOR THE PROJECT AND SITE SPECIFICALLY IDENTIFIED HEREIN. THIS DRAWING IS VALIDATED TO THE EXTENT OF THE INFORMATION PROVIDED AND DOES NOT REPRESENT A WARRANTY OR GUARANTEE OF ANY KIND. THE USER SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY PERMITS AND APPROVALS FROM ALL APPLICABLE AGENCIES AND AUTHORITIES. THE USER SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY PERMITS AND APPROVALS FROM ALL APPLICABLE AGENCIES AND AUTHORITIES. THE USER SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY PERMITS AND APPROVALS FROM ALL APPLICABLE AGENCIES AND AUTHORITIES.				9913705R3			